

MECHANICAL CHARACTERISTICS

Outer Diameter, inch (mm)	0.21 (5.33)
Minimum Bend Radius, inch (mm)	0.38 (9.65)
Flexures	10,000
Weight, grams/ft. (meter)	22 (72.2)

ELECTRICAL CHARACTERISTICS

Impedance(ohms)	50
Frequency Range (GHz)	0.05 - 26.5
Velocity of Propagation	77%
Capacitance, pF/ft. (pF/meter)	26.8 (87.93)
Shielding Effectiveness, dB @ 1GHz	>100
Maximum Insertion Loss , dB/ft. (dB/meter)	Frequency

Insertion Loss per Catalog
1.0 GHz
10.0 GHz
18.0 GHz
26.5 GHz
40.0 GHz
50.0 GHz
N/A ()
N/A ()

Phase Stability Versus Flexure	10 GHz: 3 ⁰
	18 GHz: 5 ⁰
VSWR	Based on connector selections.

ENVIRONMENTAL CHARACTERISTICS

Temperature Range(Deg C)	-65/+165
--------------------------	----------

MATERIALS

Outer jacket	Fluorinated Ethylene Propylene (FEP)
Braid	SPC Braid
Outer Conductor	Silver plated copper tape
Dielectric	LD PTFE
Center Conductor	Solid SPC


CUTAWAY



**Not typical for UGN070D


CHARTS

MAXIMUM INSERTION LOSS



Insertion Loss Chart

Phase Chart



Power Chart

Average Power Handling, Watts CW at 20 degrees Celsius and Sea level

