

MECHANICAL CHARACTERISTICS

Outer Diameter, inch (mm)	0.311 (7.9)
Minimum Bend Radius, inch (mm)	1.25 (2.54)
Flexures	15,000
Weight, grams/ft. (meter)	44.5 (145.997)

ELECTRICAL CHARACTERISTICS

Impedance(ohms)	50
Frequency Range (GHz)	0.05 – 18
Velocity of Propagation	84%
Capacitance, pF/ft. (pF/meter)	24.5 (80.38)
Shielding Effectiveness, dB @ 1GHz	>100
Maximum Insertion Loss , dB/ft. (dB/meter)	Frequency

Insertion Loss per Catalog
0.05 (0.16)
0.15 (0.49)
0.21 (0.69)
N/A ()
N/A ()
N/A ()
N/A ()

1.0 GHz
10.0 GHz
18.0 GHz
26.5 GHz
40.0 GHz
50.0 GHz

Phase Stability Versus Flexure	10 GHz: 5 ⁰
	18 GHz: 2 ⁰

VSWR	Based on connector selections.
------	--------------------------------

ENVIRONMENTAL CHARACTERISTICS

Temperature Range(Deg C)	-65/+165
--------------------------	----------

MATERIALS

Outer jacket	Fluorinated Ethylene Propylene (FEP)
Braid	SPC Braid
Outer Conductor	Silver plated copper tape
Dielectric	ULD PTFE
Center Conductor	Solid SPC


CUTAWAY



**Not typical for UGN070D


CHARTS

MAXIMUM INSERTION LOSS



Insertion Loss Chart

Phase Chart



Power Chart

Average Power Handling, Watts CW at 20 degrees Celsius and Sea level

